

View Online at <https://aerobasegroup.com/nsn/4730-00-133-3205>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

450.0 degrees fahrenheit single response

**Connection Style:**

Swivel nut, flare (tube) style 3 optional end 1st end

**Leg Length:**

3.438 inches 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Maximum Operating Pressure:**

1000.0 pounds per square inch single response

**Thread Size:**

1.625 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Inside Diameter Hose Accommodated:**

1.125 inches 2nd end

**Outside Diameter Hose Accommodated:**

1.359 inches 2nd end

**Outside Diameter Tube Accommodated:**

1.250 inches 1st end

**Material:**

Steel

**Material Specification:**

Mil-t-8808, comp federal specification single material response and qq-s-763, class federal specification 1st material response and qq-s-763, class federal specification 2nd material response and qq-w-423, class 305, cond a federal specification 3rd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-t-8808, comp 321, ty1 federal specification single treatment response and qq-s-763, class 321, cond a federal specification 1st treatment response and qq-s-763, class 304, cond a federal specification 2nd treatment response and qq-w-423, class 305, cond a federal specification 3rd treatment response

**Thread Series Designator:**

Unj 1st end

**Furnished Items And Quantity:**

1 hose coupling sleeve and 1 hose coupling nut

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-t-8808 spec.