Pipe To Tube Straight Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-142-2919

Pipe Size Accommodated: 0.250 inches 2nd end Connection Style: Streamlined w/ two brazing rings (tube) 1st end Connection Type: Unthreaded internal tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Maminallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit of Measure: Demilitarization: No Fig:	
Connection Style: Streamlined w/ two brazing rings (tube) 1st end Connection Type: Unthreaded internal tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Material: 1.250 inches Material: Copper alloy Media For Which Designed: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Pipe Size Accommodated:
Streamlined w/ two brazing rings (tube) 1st end Connection Type: Unthreaded internal tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.250 inches 2nd end
Connection Type:Unthreaded internal tube 1st endMaximum Operating Pressure:3000.0 pounds per square inch single responseThread Size:0.250 inches 2nd endOutside Diameter Tube Accommodated:0.540 inches 1st endNominallength:1.250 inchesMaterial:Copper alloyMedia For Which Designed:Water-oil-gas single responseThread Series Designator:Npt 2nd endReference Number Differentiating Characteristics:As differentiated by tubesizes an inserted ringsShelf Life:N/aUnit Of Measure:-No	Connection Style:
Unthreaded internal tube 1st end Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: 	Streamlined w/ two brazing rings (tube) 1st end
Maximum Operating Pressure:3000.0 pounds per square inch single responseThread Size:0.250 inches 2nd endOutside Diameter Tube Accommodated:0.540 inches 1st endNominallength:1.250 inchesMaterial:Copper alloyMedia For Which Designed:Water-oil-gas single responseThread Series Designator:Npt 2nd endReference Number Differentiating Characteristics:As differentiated by tubesizes an inserted ringsShelf Life:N/aUnit Of Measure:Demilitarization:No	Connection Type:
3000.0 pounds per square inch single response Thread Size: 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Nyt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: 	Unthreaded internal tube 1st end
Thread Size:0.250 inches 2nd endOutside Diameter Tube Accommodated:0.540 inches 1st endNominallength:1.250 inchesMaterial:Copper alloyMedia For Which Designed:Water-oil-gas single responseThread Series Designator:Npt 2nd endReference Number Differentiating Characteristics:As differentiated by tubesizes an inserted ringsShelf Life:N/aUnit Of Measure:Demilitarization:No	Maximum Operating Pressure:
 0.250 inches 2nd end Outside Diameter Tube Accommodated: 0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No 	3000.0 pounds per square inch single response
Outside Diameter Tube Accommodated: 0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Size:
0.540 inches 1st end Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Nyt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.250 inches 2nd end
Nominallength: 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outside Diameter Tube Accommodated:
 1.250 inches Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No 	0.540 inches 1st end
Material: Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nominallength:
Copper alloy Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: The Demilitarization: No	1.250 inches
Media For Which Designed: Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:
Water-oil-gas single response Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Copper alloy
Thread Series Designator: Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Media For Which Designed:
Npt 2nd end Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Water-oil-gas single response
Reference Number Differentiating Characteristics: As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:
As differentiated by tubesizes an inserted rings Shelf Life: N/a Unit Of Measure: Demilitarization: No	Npt 2nd end
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reference Number Differentiating Characteristics:
N/a Unit Of Measure: Demilitarization: No	As differentiated by tubesizes an inserted rings
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A080b0	A080b0