NSN 4730-00-145-0701

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-145-0701

Balan Concentric Hole Depth: 2.250 Inches Concentric Hole Diameter: 0.250 Inches Overall Length: 7.460 Inches First End Connection Type: Threaded advanal tube First End Connection Type: Threaded advanal tube First End Style Designator: Plain First End Thread Class: 2a Right-hand Second End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Ox00 Inches Cotter Pin Hole Dameter: 0.000 Inches Cotter Pin Hole Dameter: 1.000 Inches First End Thread Length: 1.500 Inches Wieth Across Flats: 1.600 Inches Distance From Wortching Feature: Berkeen 0.95	Body Style:
Concentric Hole Dameter: 2.250 inches Concentric Hole Dameter: 0.250 inches Varial Laught: 7.460 inches First End Connection Type: Threaded external tube First End Style Designator: Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Outogo inches Outogo inches Outogo inches Vieth Across Flats: 1.500 inches First End To Hole Center: 0.500 inches First Diateer From Morthing Feature: 0.500 inches First Diateer From Wenching Feature: 0.500 inches First End To Hole Center: 0.500 inches First Diateer From Wenching Feature: 0.500 inches	
2420 indes Concentric Hole Diameter: 2420 indes Coveral Langth: 7460 indes First End Connection Type: First End Style Designator: Plain First End Thread Class: 24 First End Thread Class: 24 First End Thread Direction: Plain First End Thread Direction: Plain Coceed End Style Designator: Plain Coc	
Concentric Hole Diameter:0.250 inchesOveral Length:7.460 inchesFirst End Connection Type:Threaded extenul tubeFirst End Shyle Designator:PlainFirst End Thread Class:2aFirst End Thread Direction:Right-handSecond End Connection Type:Threaded internal tubeSecond End Style Designator:PlainFirst End Style Designator:PlainRight-handSecond End Connection Type:Threaded internal tubeSecond End Style Designator:PlainFirst End Seat Radius:0.060 inchesCotter Pin Hole Diameter:0.203 inchesWitch Across Fist:1.500 inchesFirst End Thread Length:1.620 inchesViertuching Feature Style:HexagonDistance From Morthing Feature:Botwane 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.203 inchesFirst End Fluid Hole Diameter:0.303 inchesFirst End Thread Length:1.620 inchesFirst End Thread Length:1.620 inchesFirst End To Hole Center:0.500 inchesFirst End To Hole Center:0.303 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.303 inchesFirst Endial Huld Hole Diameter:0.303 inchesFirst Endial Fluid Hole Center To End Of Bi	
0.250 inches 7.400 inches First End Connection Type: Threaded external tube First End Style Designator: Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Thread Direction: Right-hand Second End Style Designator: Plain Threaded internal tube Second End Style Designator: Plain Test End Seat Radius: 0.050 inches Octor Pin Hole Diameter: 0.0203 inches Witch Across Flats: 1.500 inches First End Thread Length: 1.620 inches First End Stort Bot End To Hole Center: 0.500 inches First End From Bot End To Hole Center: 0.500 inches First End From Bot End To Hole Center: 0.500 inches First End From Bot End To Hole Center: 0.500 inches First Rad	
Overall Length:7.460 inchesFirst End Connection Type:Threaded external tubeFirst End Style Designator:PlainFirst End Thread Class:2aFirst End Thread Direction:Right-handSecond End Connection Type:Threaded internal tubeSecond End Style Designator:PlainFirst End Ster Dation:Outcome Style Designator:PlainFirst End Ster Radius:Outcome StateOutcome StateOutcome StateOutcome StateVietth Across Flats:1.500 inchesFirst End Thread Length:1.620 inchesVietnehme Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst End Trom Surface Of Wrenching Feature To End Of First Diameter:1.510 inchesFirst End Trom Bolt End To Hole Center:0.500 inchesFirst End Trom Surface Of Wrenching Feature To End Of First Diameter:0.500 inchesFirst End Trom Diet End To Hole Center To End Of First Diameter:1.510 inchesFirst End From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.510 inchesFirst End First Radial Hole Center To End Of Birst Diameter:0.520 inchesDistance From First Radial Hole Center To End Of Birst Diameter:0.520 inchesFirst End First Radial Hole Center To End Of Birst Diameter:0.520 inchesDistance Form First Radial Hole Center To End Of Birst Diameter:0.52	
7.480 inches First End Connection Type: Threaded external tube First End Style Designator: Plain First End Thread Class: 2a First End Thread Class: 2a First End Thread Class: Plain Threaded internal tube Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Witch Across Flats: 1.500 inches First End Thread Length: 1.620 inches Wenching Feature Style: Hexagon Distance From Bot End To Hole Center: 0.500 inches First End Style Designatore: 1.500 inches First End First Badial Hule Center To End Of First Diameter: 0.300 inches <	
First End Connection Type: Threaded external tube First End Style Designator: Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Vidth Across Flats: 1.500 inches First End Thread Length: 1.620 inches Vidth Across Flats: 1.620 inches Piste End Thread Length: 1.620 inches Vidth Across Flats: 1.620 inches Piste End Thread Length: 1.620 inches Piste End Thread Length Feature: 1.620 inches Piste End Thread Length Feature: 1.620 inches	-
Threaded external tube First End Style Designator: Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Stead Radius: Octor Pin Hole Diameter: Octor Pin Hole Diameter: Octor Pin Hole Diameter: 1.500 inches First End Thread Length: 1.620 inches First Diameter From Bolt End To Hole Center: 0.500 inches First Zin Thread Length From Lengthere Econt Of End Of First Diameter: 0.500 inches Euger From Bearing Surfa	
Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Vidth Across Flats: 1.500 inches First End Steat Radius: 0.203 inches Witch Across Flats: 1.620 inches First End Thread Length: 1.620 inches First End Thread Length: 1.620 inches First End Thread Length: 1.620 inches Pistance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: 0.500 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid Hole Diameter: 0.250 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid H	
Plain First End Thread Class: 2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Vidth Across Flats: 1.500 inches First End Steat Radius: 0.203 inches Witch Across Flats: 1.620 inches First End Thread Length: 1.620 inches First End Thread Length: 1.620 inches First End Thread Length: 1.620 inches Pistance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: 0.500 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid Hole Diameter: 0.250 inches First Adial Fluid Hole Diameter: 0.130 inches First Adial Fluid H	First End Style Designator:
2a First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.000 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.500 inches First End Thread Length: 1.500 inches Piste End Thread Length: 1.500 inches Piste End Thread Length: 1.500 inches Piste End Thread Length: 1.500 inches Pistence From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: 0.500 inches Pistence From Bolt End To Hole Center: 0.500 inches Pistence From Wrenching Feature: 0.301 inches First Zulai Fluid Hole Diameter: 0.302 inches Pistence From First Radial Hole Center To End Of First Diameter: 0.301 inches First Cadial Fluid Hole Diameter: 0.302	
First End Thread Direction: Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.520 inches Wernching Feature Style: Hexagon Distance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: 1.510 inches First Diameter From Solt End To Hole Center: 0.500 inches First Diameter From Bolt End To Hole Center: 0.500 inches First Radial Fluid Hole Diameter: 0.510 inches First Radial Fluid Hole Diameter: 0.510 inches Cotter From First Radial Hole Center To End Of First Diameter: 0.250 inches First Radial Fluid Hole Center To End Of Bolt: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 0.250 inches Distance From First Radial Hole Cente	
Right-hand Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End State State: 1.600 inches Piste End Thread Length: 1.620 inches Wernehing Feature Style: Hexagon Distance From Boit End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: Betwen 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.250 inches First Radial Fluid Hole Diameter: 0.250 inches Pista Radial Fluid Hole Diameter: 0.250 inches First Radial Fluid Hole Diameter: 0.250 inches Pista Radial Fluid Hole Center To End Of Bolt: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 0.250 inches	2a
Second End Connection Type: Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.620 inches Piste End Thread Length: 1.620 inches Pistence From Bolt End To Hole Center: 0.500 inches Piste Diameter From Wrenching Feature: Between 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.510 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 2.510 inches Lister From First Radial Hole Center To End Of Bolt: 2.510 inches	First End Thread Direction:
Threaded internal tube Second End Style Designator: Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.620 inches Pirst End Thread Length: 1.620 inches Pirst End Thread Length: 1.620 inches Pistace From Bolt End To Hole Center: 0.500 inches Pist Diameter From Wrenching Feature: 0.500 inches First Adial Fluid Hole Diameter: 0.500 inches First Radial Fluid Hole Center To End Of First Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 0.210 inches Exation First Radial Hole Center To End Of Bolt: 0.210 inches	Right-hand
Second End Style Designator:PlainFirst End Seat Radius:0.060 inchesCotter Pin Hole Diameter:0.203 inchesWidth Across Flats:1.500 inchesFirst End Thread Length:1.620 inchesWrenching Feature Style:PlexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature 10 End Of First Diameter:0.500 inchesFirst Diameter From Wrenching Feature To End Of First Diameter:0.510 inchesFirst Adial Fluid Hole Diameter:0.510 inchesFirst Radial Fluid Hole Diameter:0.520 inchesFirst Radial Fluid Hole Diameter:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Center To End Of Bolt:0.520 inchesFirst Radial Fluid Hole Cen	Second End Connection Type:
Plain First End Seat Radius: 0.060 inches Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.620 inches Wrenching Feature Style: Hexagon Distance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: Between 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 5.130 inches First Radial Fluid Hole Diameter: 0.250 inches First Radial Fluid Hole Center To End Of Bolt: 2.510 inches First Radial Fluid Hole Center To End Of Bolt: 5.210 inches	Threaded internal tube
First End Seat Radius:0.060 inchesCotter Pin Hole Diameter:0.203 inchesWidth Across Flats:1.500 inchesFirst End Thread Length:1.620 inchesWrenching Feature Style:1.620 inchesBrace From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:0.210 inchesDistance From First Radial Hole Center To End Of Bolt:0.210 inchesDistance From First Radial Hole Center To End Of Bolt:0.210 inchesDistance From First Radial Hole Center To End Of Bolt:0.210 inchesDistance From First Radial Hole Center To End Of Bolt:0.210 inches0.210 inches0.210 inches0.210 inches <th>Second End Style Designator:</th>	Second End Style Designator:
0.060 inchesCotter Pin Hole Diameter:0.203 inchesWidth Across Flats:1.500 inchesFirst End Thread Length:1.620 inchesWrenching Feature Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.520 inchesFirst Radial Fluid Hole Diameter:0.520 inchesFirst Radial Fluid Hole Diameter:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inchesDistance From First Radial Hole Center To End Of Bolt:0.520 inches0.520 inches <th>Plain</th>	Plain
Cotter Pin Hole Diameter: 0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.620 inches Wrenching Feature Style: Hexagon Distance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: Between 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 5.130 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches	First End Seat Radius:
0.203 inches Width Across Flats: 1.500 inches First End Thread Length: 1.620 inches Wrenching Feature Style: 1.620 inches Hexagon Distance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: Between 0.995 inches and 0.998 inches Ength From Bearing Surface Of Wrenching Feature To End Of First Diameter: 5.130 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches	0.060 inches
Width Across Flats:1.500 inchesFirst End Thread Length:1.620 inchesWrenching Feature Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To End Center To End Of Bolt:5.210 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesContenting Feature To End Center To	Cotter Pin Hole Diameter:
 1.500 inches First End Thread Length: 1.620 inches First End Thread Length: 1.620 inches Wrenching Feature Style: Hexagon Distance From Bolt End To Hole Center: 0.500 inches First Diameter From Wrenching Feature: Between 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 5.130 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End: 	0.203 inches
First End Thread Length:1.620 inchesWrenching Feature Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	Width Across Flats:
1.620 inchesWrenching Feature Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	1.500 inches
Wrenching Feature Style:HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	First End Thread Length:
HexagonDistance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	1.620 inches
Distance From Bolt End To Hole Center:0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	Wrenching Feature Style:
0.500 inchesFirst Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	Hexagon
First Diameter From Wrenching Feature:Between 0.995 inches and 0.998 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	
Between 0.995 inches and 0.998 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 5.130 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:5.130 inchesFirst Radial Fluid Hole Diameter:0.250 inchesDistance From First Radial Hole Center To End Of Bolt:5.210 inchesLength From Bearing Surface Of Wrenching Feature To Bolt End:	-
5.130 inches First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
First Radial Fluid Hole Diameter: 0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
0.250 inches Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
Distance From First Radial Hole Center To End Of Bolt: 5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
5.210 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:	
Length From Bearing Surface Of Wrenching Feature To Bolt End:	
6.750 inches	
	6.750 inches

NSN 4730-00-145-0701

Fluid Passage Bolt - Page 2 of 2



Wrenching Feature Height:

0.710 inches

First End Thready Qty Per Inch (tpi):

8

First End Thread Series Designator:

Unc

First End Seat Angle:

45.0 degrees

First End Thread Size:

1.000 inches

Material:

Steel comp 1020

Material Specification:

Qq-s-634 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0