NSN 4730-00-145-4701

Fluid Passage Bolt - Page 1 of 2

0.062 inches



View Online at https://aerobasegroup.com/nsn/4730-00-145-4701

Darles Officials
Body Style:
Body wrenching
Extended Washer Diameter:
0.625 inches
Concentric Hole Diameter:
0.078 inches
Overall Length:
1.266 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Inverted flare
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded external tube
Second End Style Designator:
Plain
Second End Thread Class:
3a
3a Second End Thread Direction:
Second End Thread Direction:
Second End Thread Direction: Right-hand
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style: Extended washer
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style: Extended washer Distance From Bolt End To Hole Center:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style: Extended washer Distance From Bolt End To Hole Center: 0.562 inches
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style: Extended washer Distance From Bolt End To Hole Center: 0.562 inches First Diameter From Wrenching Feature:
Second End Thread Direction: Right-hand Cotter Pin Hole Diameter: 0.062 inches Width Across Flats: 0.500 inches First End Thread Length: 0.625 inches Second End Thread Length: 0.308 inches Wrenching Feature Style: Extended washer Distance From Bolt End To Hole Center: 0.562 inches First Diameter From Wrenching Feature: 0.315 inches

NSN 4730-00-145-4701 Fluid Passage Bolt - Page 2 of 2



Distance From First Radial Hole Center To End Of Bolt:
0.585 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
0.723 inches
Wrenching Feature Height:
0.238 inches
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
First End Thread Series Designator:
Unf
First End Seat Angle:
15.0 degrees
First End Thread Size:
0.312 inches
Second End Thread Size:
0.250 inches
Second End Thread Series Designator:
Unf
Material:
Titanium alloy, ams 4928
Material Specification:
81343-ams6322 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A121a0