NSN 4730-00-159-6339

Tube Fitting Locknut - Page 1 of 1

Mil a 9625 anaa



View Online at https://aerobasegroup.com/nsn/4730-00-159-6339

| View Online at https://aeroba | usegroup.com/nsn/4730-00-159-6339 |
|--------------------------------|---|
| Thread Class: | |
| 3b | |
| Thread Direction: | |
| Right-hand | |
| Nut Height: | |
| 0.250 inches | |
| Width Across Flats: | |
| Between 0.684 inches and 0. | .691 inches |
| Thread Series: | |
| Unf | |
| Thready Qty Per Inch (tpi): | |
| 20 | |
| Thread Size: | |
| 0.438 inches | |
| Tube Outside Diameter: | |
| 0.250 inches | |
| Criticality Code Justificatio | n: |
| Zzzw | |
| Special Features: | |
| Color blue | |
| Material: | |
| Aluminum alloy 2014 or alun | ninum alloy 2024 |
| Material Specification: | |
| Qq-a-225/4 temper t6 federal | l specification 1st material response or qq-225/6 temper t6 federal specification 2nd material response or |
| qq-a-225/6 temper t851 fede | ral specification 2nd material response |
| Surface Treatment: | |
| Anodize | |
| Surface Treatment Specific | ation: |
| Mil-a-8625, type 2 military sp | pecification single treatment response |
| Test Data Document: | |
| 36659-lc+72-1238 specificati | on (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercia | l catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performar | nce requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Departure From Cited Docu | |
| Certified free from magnetic | contamination lcpy 72-1238 fscm 36659 |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A021a0 | |
| Mil-std (military Standard): | |
| | |