

View Online at <https://aerobasegroup.com/nsn/4730-00-168-1782>

Thread Class:

3b 1st end

Maximum Operating Temp:

204.0 degrees celsius single response

Connection Style:

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

Leg Length:

1.750 inches 2nd end

Connection Type:

Threaded internal tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

Flow Angle:

45.0 degrees

Inside Diameter Hose Accommodated:

0.310 inches 2nd end

Outside Diameter Hose Accommodated:

0.575 inches 2nd end

Outside Diameter Tube Accommodated:

0.328 inches 1st end

Material:

Steel comp 304 or steel comp 304l or steel comp 316 or steel comp 321 or steel comp 347

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-83296 military specification single treatment response

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 hose coupling nut and 1 hose coupling sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-83296 spec.