

View Online at <https://aerobasegroup.com/nsn/4730-00-173-1881>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees celsius single response

End Application:

20 ton wheel mounted crane, harnischfeger model m320rt; 2320-01-442-1940, truck, cbt, (command bridge transporter); 2320-01-097-0248, 2320-01-097-0249, 2320-01-100-7672, 2320-01-097-0260, 2320-01-195-7641 hemtt family (heavy expanded mobility tactical trucks)

Connection Type:

Threaded external tube 1st end

Thread Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.750 inches 1st end

Nominallength:

2.000 inches

Material Specification:

66 federal standard single material response

Media For Which Designed:

Air 2nd response

Surface Treatment Specification:

J514 assn standard single treatment response and mil-c-81562, type 1, cl 3 military specification single treatment response

Thread Series Designator:

Un all ends

Furnished Items And Quantity:

1 preformed packing and 1 tube coupling nut w/sleeve

Specification Data:

96906-ms51525 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

34 figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-c-81562 spec.