## NSN 4730-00-176-4617

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-176-4617

**Overall Length:** 

6.808 inches

Second End Style Designator (non-core):

Err-090

Second End Outside Diameter Tube Accommodated:

1.100 inches

**Quick Disconnect Method:** 

Push-pull all ends

**Second Fluid End Connection Type:** 

Unthreaded external tube

**Maximum Operating Temp:** 

71.1 degrees celsius single response

**Connection Style:** 

Beaded first fluid end connection

**Connection Type:** 

Unthreaded external tube second fluid end connection

**Features Provided:** 

Self-sealing

Second End Relationship With First End:

Not identical

Maximum Operating Pressure And Media For Which Designed:

50.0 pounds per square inch fuel/oil, hydrocarbon

**Maximum Operating Pressure:** 

50.0 pounds per square inch single response

**Mounting Flange Location:** 

Second leg

**Maximum Operating Tempurature And Media For Which Designed:** 

71.1 degrees celsius fuel/oil, hydrocarbon

Outside Diameter Tube Accommodated:

1.100 inches all ends

Material:

Aluminum alloy

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625 military specification single treatment response

Style Designator:

Coupling assembly

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 4730-00-176-4617

Quick Disconnect Coupling Assembly - Page 2 of 2



Der	nilit	ariz	atio	n:

Yes - demil/mli

Fiig:

A531s0

Mil-std (military Standard):

Mil-a-8625 spec.