NSN 4730-00-177-8613

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-177-8613
Body Style:
Body wrenching
Concentric Hole Depth:
2.062 inches
Concentric Hole Diameter:
0.295 inches
Overall Length:
2.670 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
2a
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded external tube
Second End Style Designator:
Flared
Second End Thread Class:
2a
Second End Thread Direction:
Right-hand
Width Across Flats:
0.875 inches
First End Thread Length:
0.312 inches
Second End Thread Length:
0.240 inches
Wrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature:
0.738 inches
Second Diameter From Wrenching Feature:
0.912 inches

Third Diameter From Wrenching Feature:

0.750 inches

Fourth Diameter From Wrenching Feature:

0.812 inches

Fifth Diameter From Wrenching Feature:

0.485 inches

NSN 4730-00-177-8613 Fluid Passage Bolt - Page 2 of 2



Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0.062 inches
Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:
0.375 inches
Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:
0.822 inches
Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:
1.220 inches
Length From Bearing Surface Of Wrenching Feature To End Of Fifth Diameter:
1.375 inches
First Radial Fluid Hole Diameter:
1.150 inches
Distance From First Radial Hole Center To End Of Bolt:
1.062 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
1.689 inches
Wrenching Feature Height:
0.438 inches
First End Thread Series Designator:
Unf
First End Thread Size:
0.562 inches
Second End Seat Angle:
45.0 degrees
Second End Thread Size:
0.562 inches
Second End Thread Series Designator:
Unf
Material:
Aluminum
Surface Treatment:
Anodize
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A121a0