

View Online at <https://aerobasegroup.com/nsn/4730-00-186-3028>

End Application:

2 1/2 ton, 6x6, m series truck

External Thread Size:

3/4-14

Internal Thread Size:

3/8-18

Working Pressure And Service Type:

150.0 pounds per square inch steam

Working Temperature And Service Type:

Not rated

External Screw Thread Series Designator:

Npt

External Thread Direction:

Right-hand

Internal Screw Thread Series Designator:

Npt

Internal Thread Direction:

Right-hand

Material:

Iron, qq-i-652-canceled or iron, malleable, qq-i-666, grade 1

Material:

Iron cast uns f11401 or iron cast uns f11701 or iron cast uns f12101 or iron cast uns f12401 or iron cast uns f12801 or iron cast uns f13101 or iron cast uns f13501 or iron cast uns f13801 or iron cast uns f14101 or iron cast uns f22400

Material Specification:

Qq-i-652-canceled federal specification 1st material response and qq-i-666, grade 1 federal specification 2nd material response

Surface Treatment:

Zinc

Style Designator:

Outside hexagon or octagon (partial or full thread optional)

Surface Treatment:

Zinc, astm a153

Specification Or Standard:

B type and d class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T385-k