

View Online at <https://aerobasegroup.com/nsn/4730-00-186-9963>

Thread Class:

3a 1st end

Maximum Operating Temp:

225.0 degrees fahrenheit 1st response

End Application:

F-18 aircraft and hawk msl mim-23, ised on airplane, utility u-2 (beech), reconnaissance, utility, ru-21 (beech)

Connection Style:

Plain (pipe) 2nd end

Leg Length:

1.062 inches 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Special Features:

Grumman aerospace a-10 aircraft

Material:

Aluminum alloy 2014 or aluminum alloy 2024

Material Specification:

Qq-a-367 federal specification single material response or qq-a-225/6, t6 federal specification single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms20822 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.