NSN 4730-00-193-0883

Pipe Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-193-0883

| External Thread Size: | |
|---|-----------|
| 1-1/4-11-1/2 | |
| Internal Thread Size: | |
| 1-11-1/2 | |
| Working Pressure And Service Type: | |
| 150.0 pounds per square inch steam | |
| Working Tempurature And Service Type: | |
| Not rated | |
| External Screw Thread Series Designator: | |
| Npt | |
| External Thread Direction: | |
| Right-hand | |
| Internal Screw Thread Series Designator: | |
| Npt | |
| Internal Thread Direction: | |
| Right-hand | |
| Material: | |
| Iron, malleable, astm a197 and iron, malleable, qq-i-666, grade 1 and iron, malleable, qq-i-666, grade 2 or iron, cast, qq-i-6 | 52, class |
| 20 or iron, cast, qq-i-652, class 25 or iron, cast, qq-i-652, class 30 | |
| Material: | |
| Iron, malleable, astm a197 and iron cast uns f22400 and iron cast uns f22200 or iron cast uns f11401 or iron cast uns f11701 or | iron cast |
| uns f12101 | |
| Material Specification: | |
| Qq-i-666, grade 1 federal specification 2nd material response and qq-i-666, grade 2 federal specification 3rd material response | and |
| qq-i-652, class 20 federal specification 4th material response and qq-i-652, class 25 federal specification 5th material response | and |
| qq-i-652, class 30 federal specification 6th material response | |
| Style Designator: | |
| Outside hexagon or octagon (partial or full thread optional) | |
| Specification Or Standard: | |
| 2 type and c style | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| T385-k | |