

View Online at <https://aerobasegroup.com/nsn/4730-00-193-3197>

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

Between 0.141 inches and 0.151 inches

**Width Across Flats:**

Between 1.801 inches and 1.815 inches

**First End Thread Length:**

0.958 inches

**Wrenching Feature Style:**

Octagon

**Distance From Bolt End To Hole Center:**

Between 0.170 inches and 0.180 inches

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 33.0 rockwell c

**First End Thread Qty Per Inch (tpi):**

12

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

1.250 inches

**Material:**

Steel

**Material Specification:**

Mil-s-5002 military specification single material response or mil-s-6049 military specification single material response or mil-s-6098 military specification single material response or mil-s-8503 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0

**Mil-std (military Standard):**

Mil-s-5002 spec.