NSN 4730-00-194-0209

Pipe Bushing - Page 1 of 1

Mil-f-5509 spec.



View Online at https://aerobasegroup.com/nsn/4730-00-194-0209

| End Application: |
|--|
| Grumman aerospace a-10 aircraft |
| External Thread Size: |
| 3/4-14 |
| Internal Thread Size: |
| 3/8-18 |
| Working Pressure And Service Type: |
| 3000.0 pounds per square inch liquid |
| Working Tempurature And Service Type: |
| 225.0 degrees fahrenheit oxygen, gaseous |
| External Screw Thread Series Designator: |
| Anpt |
| External Thread Direction: |
| Right-hand |
| Internal Screw Thread Series Designator: |
| Anpt |
| Internal Thread Direction: |
| Right-hand |
| Material: |
| Aluminum alloy, qq-a-225/4, alloy 2014, t6 or aluminum alloy, qq-a-225/6, alloy 2024, t6 |
| Material: |
| Aluminum alloy 2014 or aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/4, alloy 2014, t6 federal specification 1st material response and qq-a-225/6, alloy 2024, t6 federal specification 2nd material |
| response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Outside hexagon or octagon (partial or full thread optional) |
| Surface Treatment: |
| Anodized, mil-a-8625, type 2, class 2 |
| Specification Data: |
| 88044an912 government standard and 81343-as4842 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T385-k |
| Mil-std (military Standard): |