NSN 4730-00-202-9601

Steam Trap - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-202-9601

Body Design: Straight pattern Material And Location: Steel, corrosion resisting working parts Design Type: Thermostatic Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inet/outlet Connection Similarity: Identical Inter/outlet Connection Type: Socket welding Inter/outlet Connection Type: Socket welding Inter/outlet Connection Thread Provision: Unthreaded Inter Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: r Penilitarization: No Fig: State Solute Solute Solute	
Material And Location: Steel, corrosion resisting working parts Design Type: Thermostatic Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inet/outlet Connection Similarity: Identical Inter/outlet Connection Type: Socket welding Inter/outlet Connection Type: Socket welding Inter/outlet Connection Type: Socket welding Inter/outlet Connection Type: Context Ion In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Body Design:
Steel, corrosion resisting working parts Design Type: Thermostatic Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inter/outlet Connection Similarity: Identical Inter/outlet Connection Pipe Size: 0.500 inches Inter/outlet Connection Type: Socket welding Inter/outlet Connection Type: Socket welding Inter/outlet Connection Thread Provision: Unthreaded Inter Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Straight pattern
Design Type: Thermostatic Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in, 15 psi Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Material And Location:
Themostatic Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Steel, corrosion resisting working parts
Maximum Steam Working Pressure: 15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: To To Pemilitarization: No Fig:	Design Type:
15.0 pounds per square inch Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in, 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thermostatic
Strainer: Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Steam Working Pressure:
Included Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	15.0 pounds per square inch
Rated Capacity At Maximum Working Pressure: Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Strainer:
Not rated Inlet/outlet Connection Similarity: Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Conter side Inlet Location In Relation To Installed Position: Center side Cage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Included
Interformed Inter	Rated Capacity At Maximum Working Pressure:
Identical Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Outhreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in, 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not rated
Inlet/outlet Connection Pipe Size: 0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inlet/outlet Connection Similarity:
0.500 inches Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: No No Fig:	Identical
Inlet/outlet Connection Type: Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inlet/outlet Connection Pipe Size:
Socket welding Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.500 inches
Inlet/outlet Connection Thread Provision: Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inlet/outlet Connection Type:
Unthreaded Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Socket welding
Inlet Location In Relation To Installed Position: Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inlet/outlet Connection Thread Provision:
Center side Outlet Location In Relation To Installed Position: Center side Gage Glass: Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Unthreaded
Outlet Location In Relation To Installed Position: Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inlet Location In Relation To Installed Position:
Center side Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Center side
Gage Glass: Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outlet Location In Relation To Installed Position:
Not included Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Center side
Surface Treatment: Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No	Gage Glass:
Any acceptable Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not included
Reference Number Differentiating Characteristics: 1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
1/2 in., 15 psi Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Any acceptable
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reference Number Differentiating Characteristics:
N/a Unit Of Measure: Demilitarization: No Fiig:	1/2 in., 15 psi
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
Т359-b	Fiig:
	Т359-b