

View Online at <https://aerobasegroup.com/nsn/4730-00-203-6047>

Bolt Circle Diameter:

2.625 inches

Flange Diameter:

3.750 inches

Thickness:

Between 0.687 inches and 0.734 inches

Socket Diameter:

0.540 inches

Bore Diameter:

0.391 inches

Pipe Size For Which Designed:

0.250 inches

Bolt Hole Quantity:

3

Bolt Hole Diameter:

Between 0.525 inches and 0.562 inches

Neck Height:

Between 0.438 inches and 0.500 inches

Flange Section Style:

Plain face, socket brazing neck

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

400.0 pounds per square inch air and 200.0 pounds per square inch steam and 400.0 pounds per square inch gas and 200.0 pounds per square inch steam and 400.0 pounds per square inch gas and 400.0 pounds per square inch oil and 400.0 pounds per square inch water

Maximum Operating Temperature And Media For Which Designed:

150.0 degrees fahrenheit air and 425.0 degrees fahrenheit steam and 150.0 degrees fahrenheit gas and 150.0 degrees fahrenheit oil and 150.0 degrees fahrenheit water

Material:

Copper alloy

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type and 400 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300

Mil-std (military Standard):

Mil-f-20042 spec.