## NSN 4730-00-203-9460

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-203-9460

## Pipe Size Accommodated:

0.500 inches all ends

Second End Style Designator (non-core):

Err-090

**Second End Pipe Size Accommodated:** 

0.500 inches

**Quick Disconnect Method:** 

Spring push-pull all ends

**Second Fluid End Connection Type:** 

Threaded external pipe

**Connection Style:** 

Plain first fluid end connection

**Connection Type:** 

Threaded external pipe second fluid end connection

**Features Provided:** 

Self-sealing

Second End Relationship With First End:

Not identical

Maximum Operating Pressure And Media For Which Designed:

150.0 pounds per square inch any acceptable

**Maximum Operating Pressure:** 

150.0 pounds per square inch single response

**Thread Size:** 

0.500 inches second fluid end connection

**Second End Thread Size:** 

0.500 inches

**Second End Thread Series Designator:** 

Npt

Material:

Steel

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:** 

Coupling assembly

**Thread Series Designator:** 

Npt second fluid end connection

**Specification Data:** 

81349-mil-c-4109 government specification

**Specification Or Standard:** 

1 type and c class and 2 style and 2 type and c class and 1 style

## NSN 4730-00-203-9460

Quick Disconnect Coupling Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A531s0