## NSN 4730-00-203-9461

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-203-9461
Second End Style Designator (non-core):  Err-090
Err Default:
Err default
Quick Disconnect Method:
Spring push-pull all ends
Second Fluid End Connection Type:
Unthreaded external hose
End Application:
Shop equipment
Connection Style:
Plain first fluid end connection
Connection Type:
Unthreaded external hose second fluid end connection
Features Provided:
Self-sealing
Second End Relationship With First End:
Not identical
Maximum Operating Pressure And Media For Which Designed:
150.0 pounds per square inch any acceptable
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.250 inches first fluid end connection
Inside Diameter Hose Accommodated:
0.250 inches all ends
Material:
Steel
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Style Designator:
Coupling assembly
Thread Series Designator:
Npt first fluid end connection
Specification Data:
81349-mil-c-4109 government specification
Specification Or Standard:
1 type and a class and 2 style and 2 type and a class and 3 style

Shelf Life: N/a

## NSN 4730-00-203-9461

Quick Disconnect Coupling Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A531s0