

View Online at <https://aerobasegroup.com/nsn/4730-00-226-6773>

**Thread Class:**

2a center bulkhead

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

79f missile, mx peacekeeper

**Connection Style:**

Flared w/ gasket seal (boss) 2nd end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches center bulkhead

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Nominallength:**

2.740 inches

**Material:**

Stainless steel

**Material Specification:**

66, 300 series federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, ty1, or type 2 federal specification single treatment response

**Thread Series Designator:**

Unf center bulkhead

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut

**Specification Data:**

81343-j514 professional/industrial association standard

**Specification Or Standard:**

3a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.