

View Online at <https://aerobasegroup.com/nsn/4730-00-226-6773>

Thread Class:

2a center bulkhead

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

79f missile, mx peacekeeper

Connection Style:

Flared w/ gasket seal (boss) 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches center bulkhead

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Nominallength:

2.740 inches

Material:

Stainless steel

Material Specification:

66, 300 series federal standard single material response

Media For Which Designed:

Hydraulic fluid 2nd response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, ty1, or type 2 federal specification single treatment response

Thread Series Designator:

Unf center bulkhead

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut

Specification Data:

81343-j514 professional/industrial association standard

Specification Or Standard:

3a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.