

View Online at <https://aerobasegroup.com/nsn/4730-00-226-6902>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

Hzn borrestal class cv

**Connection Style:**

Flared (tube) 3rd end

**Leg Length:**

1.450 inches 2nd end

**Connection Type:**

Threaded external tube 3rd end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Seat Angle:**

37.0 degrees 3rd end

**Outside Diameter Tube Accommodated:**

0.500 inches 3rd end

**Material:**

Stainless steel

**Material Specification:**

66, 300 series federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 1 or 2 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve and 1 preformed packing

**Specification Data:**

96906-ms51530 government standard and 81349-mil-f-18866 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.