

View Online at <https://aerobasegroup.com/nsn/4730-00-231-5773>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

30a tank, m-60 series

Connection Style:

Flareless (tube) 2nd end

Leg Length:

1.700 inches 3rd end

Connection Type:

Threaded external tube 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches 3rd end

Seat Angle:

12.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.625 inches 2nd end

Material:

Steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 12114

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

2 ferrule sleeve and 1 locknut and 2 short coupling nut and 1 flat washer

Specification Data:

96906-ms51841 government standard

Specification Or Standard:

2 class and 4 type and 7 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.