

View Online at <https://aerobasegroup.com/nsn/4730-00-231-5773>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

30a tank, m-60 series

**Connection Style:**

Flareless (tube) 2nd end

**Leg Length:**

1.700 inches 3rd end

**Connection Type:**

Threaded external tube 2nd end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches 3rd end

**Seat Angle:**

12.0 degrees 2nd end

**Outside Diameter Tube Accommodated:**

0.625 inches 2nd end

**Material:**

Steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 12114

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

2 ferrule sleeve and 1 locknut and 2 short coupling nut and 1 flat washer

**Specification Data:**

96906-ms51841 government standard

**Specification Or Standard:**

2 class and 4 type and 7 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.