Tube Fitting Clinch Sleeve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-246-2762

| Casehard | dening Indicator: |
|------------|---|
| Casehard | lened |
| Overall L | ength: |
| Between | 0.329 inches and 0.334 inches |
| Metallic I | Hardness Rating: |
| 99.5 rock | swell b |
| Flange O | utside Diameter: |
| Between | 0.307 inches and 0.312 inches |
| Seat Ang | le In Deg: |
| 40.0 | |
| Sleeve O | utside Diameter: |
| Between | 0.246 inches and 0.249 inches |
| Hose/tub | e Outside Diameter For Which Designed: |
| 0.188 incl | hes |
| Special F | eatures: |
| Surface ti | eatment in accordance with j514 |
| Material: | |
| Steel | |
| Material: | |
| Steel | |
| Style Des | signator: |
| Flareless | |
| Specifica | ition Data: |
| 96906-ms | 51825 government standard and 81343-j514 professional/industrial association standard |
| Specifica | tion Or Standard: |
| 28 figure | |
| Shelf Life | e: |
| N/a | |
| Unit Of N | leasure: |
| | |
| Demilitar | ization: |
| No | |
| Fiig: | |
| T385-j | |