

View Online at <https://aerobasegroup.com/nsn/4730-00-248-3918>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

260.0 degrees celsius single response

**Connection Style:**

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

**Connection Type:**

Threaded internal tube 2nd end

**Thready Qty Per Inch (tpi):**

12 1st end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Inside Diameter Hose Accommodated:**

0.875 inches 2nd end

**Outside Diameter Hose Accommodated:**

1.109 inches 2nd end

**Outside Diameter Tube Accommodated:**

1.000 inches 1st end

**Nominallength:**

2.422 inches

**Special Features:**

Used on grumman a10 aircraft

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-763, cond a federal specification single material response

**Surface Treatment:**

Passivate inside

**Thread Series Designator:**

Unj 1st end

**Furnished Items And Quantity:**

1 ferrule sleeve and 1 hose coupling nut

**Specification Data:**

96906-ms27381 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-dtl-27272 spec.