Tube To Boss Straight Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-254-9354

Thread Class: 2a all ends Maximum Operating Temp: 121.0 degrees celsius single response Connection Style: Flared (tube) 1st end Connection Type: Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Curface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Singli Contexet Standard State Stat	
Maximum Operating Temp: 121.0 degrees celsius single response Connection Style: Flared (tube) 1st end Connection Type: Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Seleve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: " Thread Seleve: Pamiliarization: No Fig:	Thread Class:
121.0 degrees celsius single response Connection Style: Flared (tube) 1st end Connection Type: Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: 3.610 inches Material:	2a all ends
Connection Style:Flared (tube) 1st endConnection Type:Threaded external tube 1st endThready Qty Per Inch (tpi):12 all endsMaximum Operating Pressure:3000.0 pounds per square inch single responseThread Size:1.062 inches all endsSeat Angle:37.0 degrees 1st endOutside Diameter Tube Accommodated:0.750 inches 1st endNominallength:3.610 inchesMaterial:Stainless steelMedia For Which Designed:Hydraulic fluid single responseSurface Treatment:Passivate outsideThread Series Designator:Un all endsFurnished Items And Quantity:1 flared sleeve and 1 short coupling nutSpecification Data:96906-ms51526 government standardShelf Life:N/aUnit Of Measure:ToToFurilitarization:NoFig:	Maximum Operating Temp:
Flared (tube) 1st end Connection Type: Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No	121.0 degrees celsius single response
Connection Type: Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Connection Style:
Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Flared (tube) 1st end
Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Type:
12 all ends Maximum Operating Pressure: 3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: 3.6	Threaded external tube 1st end
Maximum Operating Pressure:3000.0 pounds per square inch single responseThread Size:1.062 inches all endsSeat Angle:37.0 degrees 1st endOutside Diameter Tube Accommodated:0.750 inches 1st endNominallength:3.610 inchesMaterial:Stainless steelMedia For Which Designed:Hydraulic fluid single responseSurface Treatment:Passivate outsideFurnished Items And Quantity:1 flared sleeve and 1 short coupling nutSpecification Data:96906-ms51526 government standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
3000.0 pounds per square inch single response Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	12 all ends
Thread Size: 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Maximum Operating Pressure:
 1.062 inches all ends Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig: 	3000.0 pounds per square inch single response
Seat Angle: 37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: 3.610 inches 3.610 inches Material: 3.610 inches 3.610 inches 3.6	Thread Size:
37.0 degrees 1st end Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: 3.610 inches Material: Stainless steel Media For Which Designed: Media For Which Des	1.062 inches all ends
Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Seat Angle:
0.750 inches 1st end Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	37.0 degrees 1st end
Nominallength: 3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outside Diameter Tube Accommodated:
3.610 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.750 inches 1st end
Material: Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Nominallength:
Stainless steel Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	3.610 inches
Media For Which Designed: Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
Hydraulic fluid single response Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Stainless steel
Surface Treatment: Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which Designed:
Passivate outside Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hydraulic fluid single response
Thread Series Designator: Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Un all ends Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate outside
Furnished Items And Quantity: 1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
1 flared sleeve and 1 short coupling nut Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Un all ends
Specification Data: 96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Furnished Items And Quantity:
96906-ms51526 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 flared sleeve and 1 short coupling nut
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	96906-ms51526 government standard
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A080b0	Fiig:
	A080b0