

View Online at <https://aerobasegroup.com/nsn/4730-00-273-2341>

Body Style:

Plain

Concentric Hole Depth:

2.050 inches

Concentric Hole Diameter:

Between 0.105 inches and 0.110 inches

Overall Length:

3.828 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded internal tube

Second End Style Designator:

Double compression

Second End Thread Class:

3b

Second End Thread Direction:

Right-hand

Second End Seat Radius:

0.062 inches

Cotter Pin Hole Diameter:

Between 0.141 inches and 0.151 inches

Width Across Flats:

Between 0.928 inches and 0.940 inches

First End Thread Length:

0.543 inches

Second End Thread Length:

0.200 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

Between 0.114 inches and 0.134 inches

First Diameter From Wrenching Feature:

Between 0.623 inches and 0.624 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

3.125 inches

First Radial Fluid Hole Diameter:

Between 0.105 inches and 0.110 inches

Distance From First Radial Hole Center To End Of Bolt:

1.205 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

3.668 inches

Wrenching Feature Height:

0.160 inches

First End Thread Qty Per Inch (tpi):

18

First End Thread Series Designator:

Unf

First End Thread Size:

0.625 inches

Second End Thread Qty Per Inch (tpi):

28

Second End Thread Size:

0.250 inches

Second End Thread Series Designator:

Unjf

Special Features:

One grease fitting required, part no. Ms15001-4

Material:

Steel

Surface Treatment:

Cadmium

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0