

View Online at <https://aerobasegroup.com/nsn/4730-00-273-6566>

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

275.0 degrees fahrenheit single response

End Application:

Aircraft application

Connection Style:

Gripping nipple (nose) 2nd end

Leg Length:

3.200 inches 2nd end and 4.340 inches 2nd end

Width:

3.000 inches 1st end

Length:

3.000 inches 1st end

Flange Shape:

Rectangular with holes 1st end

Connection Type:

Threaded external hose gripping 2nd end

Maximum Operating Pressure:

50.0 pounds per square inch 3rd response

Flow Angle:

45.0 degrees

Thickness:

0.297 inches 1st end

Bolt Hole Diameter:

0.328 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 1st end

Flange Face Design:

Raised swivel 1st end

Raised Face Height:

0.072 inches 1st end

Raised Face Diameter:

2.750 inches 1st end

Inside Diameter Hose Accommodated:

1.812 inches 2nd end

Outside Diameter Hose Accommodated:

2.250 inches 2nd end

Special Features:

Elbow anodized blue, hose socket anodized gold

Material:

Aluminum alloy socket

Material Specification:

Qq-a-351, t4 federal specification single material response socket or qq-a-268, t4 federal specification single material response socket or qq-a-367, comp 5 federal specification single material response socket or qq-a-261 t6 federal specification single material response socket or qq-a-266, t6 federal specification single material response socket or qq-a267, t4 federal specification single material response socket

Media For Which Designed:

Oil 3rd response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Furnished Items And Quantity:

1 hose coupling nut

Specification Data:

96906-ms28749 government standard and 96906-27230 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.