## NSN 4730-00-274-0936

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-274-0936

Body Style:         Plain         Concentric Hole Depth:         1.312 inches         Concentric Hole Diameter:         0.297 inches         Overall Length:         1.562 inches         First End Connection Type:         Threaded external tube         First End Style Designator:         Flared         First End Thread Class:         3a         First End Thread Direction:         Right-hand         Width Across Flats:         Between 0.809 inches and 0.817 inches         First End Thread Length:         0.469 inches         Wrenching Feature Style:         Hexagon         First Diameter From Wrenching Feature:         Between 0.556 inches and 0.500 inches         Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:         0.875 inches
Concentric Hole Depth: 1.312 inches Concentric Hole Diameter: 0.297 inches 0.297 inches Overall Length: 1.562 inches First End Connection Type: Threaded external tube First End Connection Type: Threaded external tube First End Style Designator: First End Style Designator: First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
1.312 inches Concentric Hole Diameter: 0.297 inches Overall Length: 1.562 inches First End Connection Type: First End Connection Type: Threaded external tube First End Style Designator: First End Style Designator: First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.500 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Concentric Hole Diameter: 0.297 inches Overall Length: 1.562 inches First End Connection Type: First End Connection Type: Threaded external tube First End Style Designator: First End Style Designator: First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.500 inches Ength From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
0.297 inches Overall Length: 1.562 inches First End Connection Type: First End Connection Type: Threaded external tube First End Style Designator: First End Style Designator: First End Thread Class: First End Thread Class: 3a First End Thread Class: 3a First End Thread Direction: Right-hand Vidth Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Vienching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Overall Length:         1.562 inches         First End Connection Type:         Threaded external tube         First End Style Designator:         Flared         First End Thread Class:         3a         First End Thread Direction:         Right-hand         Width Across Flats:         Between 0.809 inches and 0.817 inches         First End Thread Length:         0.469 inches         Wrenching Feature Style:         Hexagon         First Diameter From Wrenching Feature:         Between 0.556 inches and 0.560 inches         Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:         0.875 inches
1.562 inches First End Connection Type: Threaded external tube First End Style Designator: Flared First End Style Designator: Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Vrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
First End Connection Type:Threaded external tubeFirst End Style Designator:FlaredFlaredFirst End Thread Class:3aFirst End Thread Direction:Right-handWidth Across Flats:Between 0.809 inches and 0.817 inchesFirst End Thread Length:0.469 inchesWrenching Feature Style:HexagonFirst Diameter From Wrenching Feature:Between 0.556 inches and 0.560 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.875 inches
Threaded external tube First End Style Designator: Flared Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
First End Style Designator:FlaredFlaredFirst End Thread Class:3a3aFirst End Thread Direction:Right-handWidth Across Flats:Between 0.809 inches and 0.817 inchesFirst End Thread Length:0.469 inchesWrenching Feature Style:HexagonFirst Diameter From Wrenching Feature:Between 0.556 inches and 0.560 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.875 inches
Flared First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.500 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
First End Thread Class: 3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
3a First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
First End Thread Direction: Right-hand Width Across Flats: Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Right-handWidth Across Flats:Between 0.809 inches and 0.817 inchesFirst End Thread Length:0.469 inchesWrenching Feature Style:HexagonFirst Diameter From Wrenching Feature:Between 0.556 inches and 0.560 inchesLength From Bearing Surface Of Wrenching Feature To End Of First Diameter:0.875 inches
Width Across Flats:         Between 0.809 inches and 0.817 inches         First End Thread Length:         0.469 inches         Wrenching Feature Style:         Hexagon         First Diameter From Wrenching Feature:         Between 0.556 inches and 0.560 inches         Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:         0.875 inches
Between 0.809 inches and 0.817 inches First End Thread Length: 0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
First End Thread Length:         0.469 inches         Wrenching Feature Style:         Hexagon         First Diameter From Wrenching Feature:         Between 0.556 inches and 0.560 inches         Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:         0.875 inches
0.469 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Hexagon <b>First Diameter From Wrenching Feature:</b> Between 0.556 inches and 0.560 inches <b>Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:</b> 0.875 inches
First Diameter From Wrenching Feature: Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Between 0.556 inches and 0.560 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.875 inches
0.875 inches
First Radial Fluid Hole Diameter:
0.250 inches
Distance From First Radial Hole Center To End Of Bolt:
Between 0.865 inches and 0.885 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
1.344 inches
Wrenching Feature Height:
0.219 inches
First End Thread Series Designator:
Unjf
First End Seat Angle:
45.0 degrees
-
First End Thread Size:
First End Thread Size: 0.562 inches
0.562 inches

## NSN 4730-00-274-0936

Fluid Passage Bolt - Page 2 of 2



Surface Treatment:

Cadmium

**Specification Data:** 

81343-as4875 professional/industrial association standard and 81343-as5161 government standard

Departure From Cited Document:

As modified by surface treatment

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-f-5509 spec.