## NSN 4730-00-277-6228

Fluid Pressure Line Multiple Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-00-277-6228 |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Overall Length:   |
| 1.125 inches  |
| Overall Width:  |
| 0.813 inches  |
| Thickness:  |
| 0.750 inches  |
| Thread Size:  |
| 0.500-20  |
| Thread Provision:   |
| Threaded  |
| End Application:  |
| Aircraft application  |
| Connection Style:   |
| Flared  |
| Bolt Hole Diameter:   |
| 0.500 inches  |
| Seat Angle In Deg:  |
| 37.0  |
| Screw Thread Series Designator:                               |
| Unf   |
| Seat:   |
| Included  |
| Deg Between Outlets:  |
| 45.0  |
| Fluid Connection Quantity:                                    |
| 1   |
| Fluid Conveyance Type And Size For Which Designed:            |
| 0.313 in. Od tube   |
| <b>Bolt Hole Flats Serrations:</b>                            |
| Provided  |
| Bolt Hole Fluid Passage:                                      |
| Provided  |
| Material:   |
| Aluminum alloy  |
| Material:   |
| Aluminum alloy  |
| Surface Treatment:  |

Anodize

## NSN 4730-00-277-6228

Mil-f-5509 spec.

Fluid Pressure Line Multiple Connector - Page 2 of 2



| Style Designator:   |
|---|
| 1 fluid connection  |
| Surface Treatment:  |
| Anodized  |
| Specification Data:   |
| 88044-an776 government standard and 81343-as4875/1 professional/industrial association standard |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| T385-g  |
| Mil-std (military Standard):  |