

View Online at https://aerobasegroup.com/nsn/4730-00-277-6228

Thread Class: 3a Thread Direction: Right-hand Overall Length: 1.125 inches Overall Width: 0.813 inches Thickness: 0.750 inches Thickness: 0.750 inches Thread Size: 0.500-20 Thread Provision: Threaded End Application: Aircraft application Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Thread Direction:Right-handOverall Length:1.125 inchesOverall Width:0.813 inchesThickness:0.813 inchesThickness:0.750 inchesThread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
Right-handOverall Length:1.125 inchesOverall Width:0.813 inchesThickness:0.813 inchesThickness:0.750 inchesThread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
Overall Length:1.125 inchesOverall Width:0.813 inchesThickness:0.501 inchesThread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
1.125 inches Overall Width: 0.813 inches District Stress Distrist Stress Distrist Stress Distr
Overall Width:0.813 inches0.813 inchesThickness:0.750 inchesThread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
0.813 inches Thickness: 0.750 inches Thread Size: 0.500-20 Thread Provision: Threaded End Application: Aircraft application Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Thickness:0.750 inchesThread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
0.750 inches Thread Size: 0.500-20 Thread Provision: Threaded End Application: Aircraft application Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Thread Size:0.500-20Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
0.500-20 Thread Provision: Threaded Threaded End Application: Aircraft application Aircraft application Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Thread Provision:ThreadedEnd Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
Threaded End Application: Aircraft application Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf
End Application:Aircraft applicationConnection Style:FlaredBolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
Aircraft application Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Connection Style: Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Flared Bolt Hole Diameter: 0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Bolt Hole Diameter:0.500 inchesSeat Angle In Deg:37.0Screw Thread Series Designator:UnfSeat:
0.500 inches Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
Seat Angle In Deg: 37.0 Screw Thread Series Designator: Unf Seat:
37.0 Screw Thread Series Designator: Unf Seat:
Screw Thread Series Designator: Unf Seat:
Unf Seat:
Included
Deg Between Outlets:
45.0
Fluid Connection Quantity:
1
Fluid Conveyance Type And Size For Which Designed:
0.313 in. Od tube
Bolt Hole Flats Serrations:
Provided
Bolt Hole Fluid Passage:
Provided
Material:
Aluminum alloy
Material:
Aluminum alloy
Surface Treatment:
Anodize

Fluid Pressure Line Multiple Connector - Page 2 of 2



Style Designator:

1 fluid connection

Surface Treatment:

Anodized

Specification Data:

88044-an776 government standard and 81343-as4875/1 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T385-g

Mil-std (military Standard):

Mil-f-5509 spec.