## NSN 4730-00-278-5822

Anodized, mil-a-8625, type 2, class 2

Fluid Pressure Line Multiple Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-278-5822
Thread Class:
3a
Thread Direction:
Right-hand
Overall Length:
1.000 inches
Overall Width:
2.500 inches
Thickness:
0.875 inches
Thread Size:
9/16 in18
Thread Provision:
Threaded
Connection Style:
Flared
Bolt Hole Diameter:
0.563 inches
Seat Angle In Deg:
37.0
Screw Thread Series Designator:
Unf
Seat:
Included
Fluid Connection Quantity:
2
Fluid Conveyance Type And Size For Which Designed:
3/8 in. Od tube
Bolt Hole Flats Serrations:
Provided
Bolt Hole Fluid Passage:
Provided
Material:
Aluminum alloy, qq-a-225/4, alloy 2014, t6 or aluminum alloy, qq-a-225/6, alloy 2024, t6
Material:
Aluminum alloy 2014 or aluminum alloy 2024
Surface Treatment:
Anodize
Style Designator:
2 fluid connections
Surface Treatment:

## NSN 4730-00-278-5822

Fluid Pressure Line Multiple Connector - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

88044-an779 government standard and 81343-as4875/1 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T385-g

Mil-std (military Standard):

Mil-f-5509 spec.