

View Online at <https://aerobasegroup.com/nsn/4730-00-287-5115>

Body Style:

Plain

Concentric Hole Depth:

1.100 inches

Concentric Hole Diameter:

Between 0.099 inches and 0.104 inches

Overall Length:

Between 1.891 inches and 1.906 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded external tube

Cotter Pin Hole Diameter:

0.106 inches

Width Across Flats:

Between 0.740 inches and 0.752 inches

First End Thread Length:

Between 0.391 inches and 0.406 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

Between 0.141 inches and 0.156 inches

First Diameter From Wrenching Feature:

Between 0.498 inches and 0.499 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

1.250 inches

First Radial Fluid Hole Diameter:

Between 0.069 inches and 0.074 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 1.009 inches and 1.014 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.641 inches and 1.656 inches

Wrenching Feature Height:

0.242 inches

First End Thread Series Designator:

Unf

First End Thread Size:

0.500 inches

Criticality Code Justification:

Bbkl

Special Features:

Fitting part no. Nas516-1, in head

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6098 military specification single material response or mil-s-8503 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lc+77-1061 lockheed-calif mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-s-5000 spec.