NSN 4730-00-288-9526

Swivel Flange To Hose Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-288-9526

Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Gripping nipple (nose) 2nd end
Leg Length:
3.000 inches 2nd end
Width:
1.750 inches 1st end
Length:
1.750 inches 1st end
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Threaded external hose gripping 2nd end
Maximum Operating Pressure:
800.0 pounds per square inch 2nd response
Flow Angle:
45.0 degrees
Thickness:
0.234 inches 1st end
Bolt Hole Diameter:
0.216 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.312 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
1.312 inches 1st end
Flange Face Design:
Raised swivel 1st end
Raised Face Height:
0.063 inches 1st end
Raised Face Diameter:
1.500 inches 1st end
Inside Diameter Hose Accommodated:
0.875 inches 2nd end
Outside Diameter Hose Accommodated:
1.234 inches 2nd end

Material:

Aluminum alloy

Material Specification:

Qq-a-351, t4 federal specification single material response socket or qq-a-268, t4 federal specification single material response socket or qq-a-261, t6 federal specification single material response socket or qq-a-261, t6 federal specification single material response socket or qq-a-266, t6 federal specification single material response socket or qq-a-267, t4 federal specification single material response socket

NSN 4730-00-288-9526

Swivel Flange To Hose Elbow - Page 2 of 2



Media For Which Designed:
Oil 3rd response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Furnished Items And Quantity:
1 hose coupling nut
Specification Data:
96906-ms28749 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A080b0
Mil-std (military Standard):
Mil-a-8625 spec.