

View Online at <https://aerobasegroup.com/nsn/4730-00-289-0359>

Thread Class:

3a 2nd end

Maximum Operating Temp:

225.0 degrees fahrenheit 1st response

End Application:

Grumman a-10 acft; support equipment, b-1 aircraft; truck, fire/crash p12; aircraft, f16; 485l tacs; galaxy c-5; hercules c-130; stratolifter c-135; phantom f-4

Connection Style:

Plain (pipe) 1st end

Connection Type:

Threaded external pipe 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 2nd end

Criticality Code Justification:

Feat

Nominallength:

1.375 inches

Special Features:

Center wrenching facility; weapon system essential

Material:

Steel comp 347

Media For Which Designed:

Oxygen, gaseous 2nd response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response inside

Thread Series Designator:

Unjf 2nd end

Specification Data:

88044-an816 government standard and 81343-as4842/1 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-14072 spec.