NSN 4730-00-289-3372

Fluid Passage Bolt - Page 1 of 2

Body Style:Body wrenching



View Online at https://aerobasegroup.com/nsn/4730-00-289-3372

Concentric Hole Diameter:
0.109 inches
Overall Length:
2.531 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded external tube
Second End Style Designator:
Second End Thread Class:
3a
Second End Thread Direction:
Right-hand
End Application:
Aircraft, c-130's, s-3a, t-37, h-46, ch-47; support equip
Width Across Flats:
Between 0.746 inches and 0.754 inches
First End Thread Length:
0.375 inches
Second End Thread Length:
1.016 inches
Wrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature:
Between 0.494 inches and 0.798 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0.188 inches
First Radial Fluid Hole Diameter:
0.062 inches
Distance From First Radial Hole Center To End Of Bolt:
Between 0.875 inches and 0.921 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
1.343 inches

NSN 4730-00-289-3372

Fluid Passage Bolt - Page 2 of 2



Wrenching Feature Height:
0.188 inches
Pressure Rating:
3000.000 pounds per square inch
First End Thread Series Designator:
Unjf
First End Thread Size:
0.500 inches
Second End Seat Angle:
37.0 degrees
Second End Thread Size:
0.438 inches
Second End Thread Series Designator:
Unjf
Criticality Code Justification:
Feat
Special Features:
Weapons system essential
Material:
Aluminum alloy
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Specification Data:
81343-as5167 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A121a0
Mil-std (military Standard):
Mil-a-8625 spec.