

View Online at <https://aerobasegroup.com/nsn/4730-00-289-4912>

**Thread Class:**

2a 1st end

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

Rg-31 mrap rcv; mrap buffalo mk2a2

**Connection Style:**

Plain (pipe) 2nd end

**Leg Length:**

1.660 inches 1st end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.750 inches 1st end

**Material:**

Steel comp 12l14

**Material Specification:**

66 federal standard single material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 3, cl 2 federal specification single treatment response

**Thread Series Designator:**

Un 1st end

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve

**Specification Data:**

96906-ms51504 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0