NSN 4730-00-293-1218

Tube Elbow - Page 1 of 2



| view Online at https://aerobasegroup.com/hsh/4730-00-293-1218 |
|---|
| Thread Class: |
| 3a all ends |
| Maximum Operating Temp: |
| 1350.0 degrees celsius single response |
| Connection Style: |
| Flareless (tube) all ends |
| Leg Length: |
| 0.940 inches 2nd end and 0.987 inches 2nd end |
| Connection Type: |
| Threaded external tube all ends |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.438 inches all ends |
| Seat Angle: |
| 12.0 degrees all ends |
| Flow Angle: |
| 90.0 degrees |
| Outside Diameter Tube Accommodated: |
| 0.250 inches all ends |
| Material: |
| Aluminum alloy 2014 |
| Material Specification: |
| Qq-a-367, t6 federal specification single material response |
| Media For Which Designed: |
| Fluid single response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2 military specification single treatment response |
| Thread Series Designator: |
| Unjf 1st end bulkhead |
| Specification Data: |
| 96906-ms21925 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A080b0

NSN 4730-00-293-1218

Tube Elbow - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.