NSN 4730-00-302-8024

Swivel Flange To Hose Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-302-8024

| Bolt Hole Quantity: | | | | | | | |
|---|--|--|--|--|--|--|--|
| 3 1st end | | | | | | | |
| Maximum Operating Temp: | | | | | | | |
| 200.0 degrees fahrenheit single response | | | | | | | |
| Connection Style: | | | | | | | |
| Gripping nipple (nose) 2nd end | | | | | | | |
| Leg Length: | | | | | | | |
| 2.800 inches 2nd end | | | | | | | |
| Flange Shape: | | | | | | | |
| Round with holes 1st end | | | | | | | |
| Connection Type: | | | | | | | |
| Threaded external hose gripping 2nd end | | | | | | | |
| Maximum Operating Pressure: | | | | | | | |
| 800.0 pounds per square inch single response | | | | | | | |
| Flow Angle: | | | | | | | |
| 90.0 degrees | | | | | | | |
| Outside Diameter: | | | | | | | |
| 3.560 inches 1st end | | | | | | | |
| Thickness: | | | | | | | |
| 0.380 inches 1st end | | | | | | | |
| Bolt Hole Diameter: | | | | | | | |
| 0.560 inches 1st end | | | | | | | |
| Bolt Circle Diameter: | | | | | | | |
| 2.440 inches 1st end | | | | | | | |
| Flange Face Design: | | | | | | | |
| Raised swivel 1st end | | | | | | | |
| Raised Face Height: | | | | | | | |
| 0.062 inches 1st end | | | | | | | |
| Raised Face Diameter: | | | | | | | |
| 1.500 inches 1st end | | | | | | | |
| Inside Diameter Hose Accommodated: | | | | | | | |
| 0.880 inches 2nd end | | | | | | | |
| Outside Diameter Hose Accommodated: | | | | | | | |
| 1.230 inches 2nd end | | | | | | | |
| Material: | | | | | | | |
| Copper alloy 903 nipple | | | | | | | |
| Material Specification: | | | | | | | |
| Sae assn standard single material response socket | | | | | | | |
| Furnished Items And Quantity: | | | | | | | |
| 1 hose socket | | | | | | | |
| Shelf Life: | | | | | | | |

N/a

NSN 4730-00-302-8024

Swivel Flange To Hose Elbow - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A080b0