

View Online at <https://aerobasegroup.com/nsn/4730-00-308-3322>

**Body Style:**

Shoulder

**Concentric Hole Depth:**

1.531 inches

**Concentric Hole Diameter:**

0.093 inches

**Overall Length:**

3.542 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal tube

**Second End Thread Class:**

2b

**Second End Thread Direction:**

Right-hand

**Second End Seat Radius:**

0.036 inches

**Cotter Pin Hole Diameter:**

0.141 inches

**Width Across Flats:**

1.062 inches

**First End Thread Length:**

0.905 inches

**Second End Thread Length:**

0.344 inches

**Wrenching Feature Style:**

Hexagon

**Distance From Bolt End To Hole Center:**

0.328 inches

**First Diameter From Wrenching Feature:**

0.748 inches

**Second Diameter From Wrenching Feature:**

0.482 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

2.367 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

2.445 inches

**First Radial Fluid Hole Diameter:**

0.064 inches

**Distance From First Radial Hole Center To End Of Bolt:**

2.011 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

3.250 inches

**Wrenching Feature Height:**

0.312 inches

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.562 inches

**Second End Thread Size:**

0.250 inches

**Second End Thread Series Designator:**

Unf

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5625, cond f military specification single material response

**Surface Treatment:**

Cadmium and chromium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl b federal specification 1st treatment response and mil-p-6871, type 2 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0

**Mil-std (military Standard):**

Mil-s-5625 spec.