

View Online at <https://aerobasegroup.com/nsn/4730-00-308-3322>

Body Style:

Shoulder

Concentric Hole Depth:

1.531 inches

Concentric Hole Diameter:

0.093 inches

Overall Length:

3.542 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded internal tube

Second End Thread Class:

2b

Second End Thread Direction:

Right-hand

Second End Seat Radius:

0.036 inches

Cotter Pin Hole Diameter:

0.141 inches

Width Across Flats:

1.062 inches

First End Thread Length:

0.905 inches

Second End Thread Length:

0.344 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

0.328 inches

First Diameter From Wrenching Feature:

0.748 inches

Second Diameter From Wrenching Feature:

0.482 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

2.367 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

2.445 inches

First Radial Fluid Hole Diameter:

0.064 inches

Distance From First Radial Hole Center To End Of Bolt:

2.011 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

3.250 inches

Wrenching Feature Height:

0.312 inches

First End Thread Series Designator:

Unf

First End Thread Size:

0.562 inches

Second End Thread Size:

0.250 inches

Second End Thread Series Designator:

Unf

Material:

Steel comp 4140

Material Specification:

Mil-s-5625, cond f military specification single material response

Surface Treatment:

Cadmium and chromium

Surface Treatment Specification:

Qq-p-416, type 2, cl b federal specification 1st treatment response and mil-p-6871, type 2 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0

Mil-std (military Standard):

Mil-s-5625 spec.