NSN 4730-00-322-7037

Tube Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-322-7037 **Thread Class:** 3b all ends **Maximum Operating Temp:** 225.0 degrees fahrenheit 1st response **Connection Style:** Flared (tube) all ends **Connection Type:** Threaded internal tube all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.875 inches all ends Seat Angle: 45.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.625 inches all ends Nominallength: 1.563 inches Material: Aluminum alloy 2014 or aluminum alloy 2024 **Material Specification:** Qq-a-225/4, t6 federal specification 1st material response or qq-a-225/6, t6 or t851 federal specification 2nd material response Media For Which Designed: Oxygen, gaseous 2nd response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2, cl 2 military specification single treatment response **Style Designator:** Plain **Thread Series Designator:** Unf 1st end **Specification Data:** 80205-nas424 professional/industrial association standard and 81343-as4875 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A080b0

NSN 4730-00-322-7037

Tube Coupling - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.