

View Online at <https://aerobasegroup.com/nsn/4730-00-335-9315>

Body Style:

Relieved

Concentric Hole Depth:

Between 0.895 inches and 0.945 inches

Concentric Hole Diameter:

Between 0.091 inches and 0.098 inches

Overall Length:

Between 1.240 inches and 1.282 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Width Across Flats:

0.562 inches

First End Thread Length:

0.500 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.371 inches and 0.374 inches

Second Diameter From Wrenching Feature:

Between 0.305 inches and 0.315 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 0.158 inches and 0.178 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 0.281 inches and 0.381 inches

First Radial Fluid Hole Diameter:

Between 0.091 inches and 0.098 inches

Distance From First Radial Hole Center To End Of Bolt:

0.845 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.045 inches and 1.085 inches

Wrenching Feature Height:

Between 0.177 inches and 0.203 inches

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

First End Thread Series Designator:

Unf

First End Seat Angle:

30.0 degrees

First End Thread Size:

0.375 inches

Material:

Steel comp 8740

Material Specification:

Qq-s-624 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0