

View Online at <https://aerobasegroup.com/nsn/4730-00-342-7808>

Body Style:

Relieved

Concentric Hole Depth:

Any acceptable

Concentric Hole Diameter:

Between 0.084 inches and 0.104 inches

Overall Length:

0.948 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

Between 0.618 inches and 0.627 inches

First End Thread Length:

Between 0.570 inches and 0.590 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.313 inches

Second Diameter From Wrenching Feature:

Any acceptable

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.072 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.162 inches

First Radial Fluid Hole Diameter:

Between 0.052 inches and 0.062 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.630 inches and 0.650 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

0.742 inches

Wrenching Feature Height:

Between 0.186 inches and 0.226 inches

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

First End Thread Series Designator:

Unf

First End Thread Size:

0.312 inches

Material:

Steel

Material Specification:

Ams 7452 assn standard single material response

Specification Data:

00198-225636 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0