

View Online at <https://aerobasegroup.com/nsn/4730-00-348-7000>

**Body Style:**

Plain

**Concentric Hole Depth:**

0.958 inches

**Concentric Hole Diameter:**

0.086 inches

**Overall Length:**

1.488 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Flared

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded external tube

**Second End Thread Class:**

3a

**Second End Thread Direction:**

Right-hand

**Width Across Flats:**

0.562 inches

**First End Thread Length:**

0.359 inches

**Second End Thread Length:**

0.188 inches

**Wrenching Feature Style:**

Hexagon

**First Diameter From Wrenching Feature:**

0.375 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.937 inches

**First Radial Fluid Hole Diameter:**

0.086 inches

**Second Radial Fluid Hole Diameter:**

0.086 inches

**Distance From First Radial Hole Center To End Of Bolt:**

1.250 inches

**Distance From Second Radial Hole Center To End Of Bolt:**

0.630 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

1.300 inches

**Wrenching Feature Height:**

0.188 inches

**First End Thread Series Designator:**

Unf

**First End Seat Angle:**

45.0 degrees

**First End Thread Size:**

0.375 inches

**Second End Thread Size:**

0.375 inches

**Second End Thread Series Designator:**

Unjf

**Material:**

Steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0

**Mil-std (military Standard):**

Mil-s-5626 spec.