

View Online at <https://aerobasegroup.com/nsn/4730-00-358-6416>

Body Style:

Relieved

Concentric Hole Depth:

Between 0.880 inches and 0.900 inches

Concentric Hole Diameter:

Between 0.189 inches and 0.199 inches

Overall Length:

Between 1.410 inches and 1.450 inches

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

Between 0.865 inches and 0.877 inches

First End Thread Length:

Between 0.336 inches and 0.356 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.479 inches and 0.483 inches

Second Diameter From Wrenching Feature:

Between 0.340 inches and 0.360 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 0.730 inches and 0.750 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 0.814 inches and 0.854 inches

First Radial Fluid Hole Diameter:

Between 0.135 inches and 0.145 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.810 inches and 0.830 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.170 inches and 1.190 inches

Wrenching Feature Height:

Between 0.240 inches and 0.260 inches

First End Thread Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unjf

First End Thread Size:

0.437 inches

Material:

Steel

Material Specification:

Ams 5735 assn standard single material response

Surface Treatment:

Passivate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0