

View Online at <https://aerobasegroup.com/nsn/4730-00-367-2891>

**Body Style:**

Relieved

**Concentric Hole Depth:**

1.007 inches

**Concentric Hole Diameter:**

0.184 inches

**Overall Length:**

1.252 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

2a

**First End Thread Direction:**

Right-hand

**Width Across Flats:**

0.750 inches

**First End Thread Length:**

0.422 inches

**Wrenching Feature Style:**

Hexagon

**First Diameter From Wrenching Feature:**

0.425 inches

**Second Diameter From Wrenching Feature:**

0.375 inches

**Third Diameter From Wrenching Feature:**

0.375 inches

**Fourth Diameter From Wrenching Feature:**

0.260 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.082 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

0.705 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:**

0.705 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:**

1.000 inches

**First Radial Fluid Hole Diameter:**

0.082 inches

**Distance From First Radial Hole Center To End Of Bolt:**

0.362 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

1.000 inches

**Wrenching Feature Height:**

0.250 inches

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.500 inches

**Special Features:**

Drilled for lock wires

**Material:**

Steel comp 302 or steel comp 303

**Material Specification:**

Mil-s-7720 military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0

**Mil-std (military Standard):**

Mil-s-7720 spec.