

View Online at <https://aerobasegroup.com/nsn/4730-00-367-2891>

Body Style:

Relieved

Concentric Hole Depth:

1.007 inches

Concentric Hole Diameter:

0.184 inches

Overall Length:

1.252 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Width Across Flats:

0.750 inches

First End Thread Length:

0.422 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.425 inches

Second Diameter From Wrenching Feature:

0.375 inches

Third Diameter From Wrenching Feature:

0.375 inches

Fourth Diameter From Wrenching Feature:

0.260 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.082 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.705 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

0.705 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

1.000 inches

First Radial Fluid Hole Diameter:

0.082 inches

Distance From First Radial Hole Center To End Of Bolt:

0.362 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.000 inches

Wrenching Feature Height:

0.250 inches

First End Thread Series Designator:

Unf

First End Thread Size:

0.500 inches

Special Features:

Drilled for lock wires

Material:

Steel comp 302 or steel comp 303

Material Specification:

Mil-s-7720 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0

Mil-std (military Standard):

Mil-s-7720 spec.