

View Online at <https://aerobasegroup.com/nsn/4730-00-388-9715>

Thread Class:

3a first fluid end connection

Overall Length:

5.602 inches

Second Leg Length:

0.911 inches

Quick Disconnect Method:

Twist-lock all ends

Mounting Flange Shape Style (non-core):

Err-090

Mounting Flange Outside Diameter:

2.750 inches

Mounting Flange Thickness:

0.012 inches

Mounting Flange Bolt Hole Quantity:

6

Mounting Flange Bolt Hole Diameter:

0.201 inches

Mounting Flange Bolt Circle Diameter:

2.315 inches

Distance From Mounting Flange To Fluid End:

1.249 inches

Maximum Operating Temp:

71.1 degrees celsius 1st response

Connection Style:

Flared first fluid end connection

Leg Length:

0.911 inches

Connection Type:

Threaded external tube first fluid end connection

Thready Qty Per Inch (tpi):

12 first fluid end connection

Second End Relationship With First End:

Identical

Maximum Operating Pressure And Media For Which Designed:

1000.0 pounds per square inch hydraulic fluid, petroleum base

Maximum Operating Pressure:

1000.0 pounds per square inch single response

Thread Size:

1.312 inches first fluid end connection

Mounting Flange Location:

First leg

Seat Angle:

37.0 degrees

Maximum Operating Temperature And Media For Which Designed:

Err-070

Outside Diameter Tube Accommodated:

1.000 inches first fluid end connection

Material:

Aluminum alloy

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Coupling assembly

Thread Series Designator:

Un first fluid end connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531s0

Mil-std (military Standard):

Mil-a-8625 spec.