NSN 4730-00-394-9864

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-394-9864 **Thread Class:** 3b first fluid end connection Second End Style Designator (non-core): Err-090 Second End Thread Class: За **Second Fluid End Connection Type:** Threaded external tube **Maximum Operating Temp:** 73.9 degrees celsius single response **Connection Style:** Plain first fluid end connection **Connection Type:** Threaded external tube second fluid end connection Second End Relationship With First End: Not identical **Maximum Operating Pressure And Media For Which Designed:** 60.0 pounds per square inch fuel/oil, hydrocarbon **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 0.750 inches second fluid end connection Second End Thread Size: 0.750 inches **Second End Thread Series Designator:** Unf Maximum Operating Tempurature And Media For Which Designed: 73.9 degrees celsius fuel/oil, hydrocarbon Material: Aluminum alloy **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Coupling assembly **Thread Series Designator:** Unf second fluid end connection

Shelf Life:

Unit Of Measure:

--

N/a

NSN 4730-00-394-9864

Quick Disconnect Coupling Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A531s0

Mil-std (military Standard):

Mil-a-8625 spec.